

LEADER REFRIGERATION MGF.INC.

NSF Bain Marie



NSFM72 S/C



NSFM48 S/C



NSFM36 S/C

Features/Benefits

Rounded inner floor/wall joins for easier cleaning. Meets NSF standards.

Uses green R141 (CFC-Free) foaming material, 2" thick. The insulation has excellent heat Isolation and outstanding temperature preservation.

Uses environmentally evaporated water from evaporator, eliminating the need for a Drainage connection and saving energy.

Removable sealed and self-closing door.

Exterior-mounted digital thermometer for monitoring the refrigerator's interior temperature.

Large evaporator provides for fast and even dynamic cooling.

Compressor is rear-mounted for a more attractive appearance.

Stainless front, side, top and inside bottom. Rust-free and durable.

MODEL	W(IN.)	D(IN.)	H(IN.)	DOORS	SHELVES	H.P.	VOLT	WEIGHT Lbs.
NSFM27S/C	27	32	45	1	1	1/4	115	141
NSFM36S/C	36	32	45	2	2	1/4	115	174
NSFM48S/C	48	32	45	2	2	1/4	115	214
NSFM60S/C	60	32	45	2	2	1/4	115	251
NSFM72S/C	72	32	45	3	3	1/4	115	285

LEADER REFRIGERATION MGF.INC.

NSF Low Boy



NSFB72 S/C



NSFB36 S/C



NSFB27 S/C

Features/Benefits

Rounded inner floor/wall joins for easier cleaning. Meets NSF standards.

Uses green R141 (CFC-Free) foaming material, 2" thick. The insulation has excellent heat

isolation and outstanding temperature preservation.

Uses environmentally evaporates water from evaporator, eliminating the need for a

drainage connection and saving energy.

Removable sealed and self-closing door.

Exterior-mounted digital thermometer for monitoring the refrigerator's interior temperature.

Large evaporator provides for fast and even dynamic cooling.

Compressor is rear-mounted for a more attractive appearance.

Stainless front, side, top, and inside bottom. Rust-free and durable

MODEL	W (IN.)	D (IN.)	H (IN.)	DOORS	SHELVES	H. P.	VOLT	WEIGHT Lbs.
NSFB27S/C	27	32	36	1	1	1/4	115	120
NSFB36S/C	36	32	36	2	2	1/4	115	149
NSFB48S/C	48	32	36	2	2	1/4	115	180
NSFB60S/C	60	32	36	2	2	1/4	115	209
NSFB72S/C	72	32	36	3	3	1/3	115	250